

## STOBITEX Wear Protection Sleeve PU-1/single

### Product information



Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

**Design:** Single- or double sided sheathes.

**Material:** Polyurethane.

**Temperature range:** Approx. -30° up to +70°C, short expose to approx. +90°C.

Part Code	Size	W mm	For 2 layer lifting mm	For 4 layer lifting mm	For roundslings ton	A mm	i mm	h mm	Weight kg/m	Delivery time
80255040105	50	5	30	-	-	50	40	10	0.85	10
8025PU15040205	50	5	-	30	-	50	40	20	0.9	10
8025PU17060125	70	5	50	-	-	70	60	12	1.25	10
8025PU17060175	70	5	-	50	-	70	60	17	1.3	10
8025PU18070125	80	5	60	-	-	80	70	12	1.3	10
8025PU18070245	80	5	-	60	-	80	70	24	1.35	10
8025PU18575175	85	5	-	-	1	85	75	12	1.35	10
8025PU19585245	95	5	-	-	2	95	85	24	1.5	10

8025PU1110100125	110	5	90	-	-	110	100	12	1.55	10
8025PU1110100175	110	5	-	-	3	110	100	174	1.6	10
8025PU1110100245	110	5	-	90	-	110	100	24	1.6	10
8025PU1145135125	145	5	120	-	-	145	135	12	2	10
8025PU1145135245	145	5	-	120	-	145	135	24	2.1	10
8025PU1170160125	170	5	150	-	-	170	160	12	2.3	10
8025PU1170160175	170	5	-	-	6	170	160	17	2.4	10
8025PU1170160245	170	5	-	150	-	170	160	24	2.4	10
8025PU1200190125	200	5	180	-	-	200	190	12	2.6	10
8025PU1200190175	200	5	-	-	8	200	190	17	2.65	10
8025PU1200190245	200	5	-	180	-	200	190	24	2.7	10
8025PU1230220365	230	5	-	-	10	230	220	36	3.5	10
8025PU1260250158	260	8	240	-	-	260	250	15	3.9	10
8025PU1290280308	290	8	-	-	15	290	280	30	4.4	10
8025PU1330320158	330	8	300	-	-	330	320	15	4.4	10
8025PU1330320308	330	8	-	300	-	330	320	30	4.8	10
8025PU1330320458	330	8	-	-	20	330	320	45	5.3	10

## Blueprint

