

Geared Trolley type 21

Product information

Low-built block trolley for hanging e.g. chain blocks and wire hoists. The trolley can be supplied with a load of 0.5 tons up to 20 tons. The trolley has corner protection which prevents the trolley from detaching from the beam and ball bearing wheels. It is easily adjustable by the left- and right-handed carrier bracket and fits most brands of hoists.

Marking: WLL, name plate and CE.

Finish: Black painted.



Part code	WLL ton	Beam width mm	Model	Minimum radius mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	M mm	O mm	P mm	R mm	Weight kg	Delivery time
502300051600430	0.5	50-160	21123A	1,250	50-160	212	20	70	88	20	56	35	32	19	264	130	100	24	104	14.3	10
502300052800430	0.5	161-280	21124A	1,250	161-280	A+57	20	70	88	20	56	35	32	19	264	130	100	24	104	15.5	10
502300101600430	1	50-160	21143A	1,250	50-160	212	20	70	88	20	51	40	32	24	264	130	100	24	104	14.3	10
502300102800430	1	161-280	21144A	1,250	161-280	A+57	20	70	88	20	51	40	32	24	264	130	100	24	104	15.5	10
502300201800430	2	64-180	21163A	1,800	64-180	248	24	100	120	24	63	51	40	32	335	165	100	31	118	25.3	10
502300203000430	2	181-300	21164A	1,800	181-300	A+76	24	100	120	24	63	51	40	32	335	165	100	31	118	27.4	10
502300301800430	3	74-180	21173A	2,200	74-180	262	28	114	137	30	78	57	46	35	380	180	165	37	130	38.2	10
502300303000430	3	181-300	21174A	2,200	181-300	A+89	28	114	137	30	78	57	46	35	380	180	165	37	130	41.2	10
502300501800430	5	82-180	21193A	2,500	82-180	270	34	140	166	32	92	64	56	42	437	215	205	41	132	56.7	10
502300503000430	5	181-300	21194A	2,500	181-300	A+97	34	140	166	32	92	64	56	42	437	215	205	41	132	60.4	10

Blueprint

