

Geared Trolley type 21

Product information

Low-built block trolley for hanging e.g. chain blocks and wire hoists. The trolley can be supplied with a load of 0.5 tons up to 5 tons. The trolley has corner protection which prevents the trolley from detaching from the beam and ball bearing wheels. It is easily adjustable by the left- and right-handed carrier bracket and fits most brands of hoists.

Marking: WLL, name plate and CE.

Finish: Black painted.



| Part Code | WLL ton | Beam width (mm) | Type | Min curve r m | B mm | C mm | Ø D mm | E mm | F mm | G mm | H mm | Ø J mm | Ø K mm | L mm | M mm | Ø O mm | P mm | R mm | Weight kg | Delivery time |
|-----------------|---------|-----------------|--------|---------------|------|------|--------|------|------|------|------|--------|--------|------|------|--------|------|------|-----------|---------------|
| 502300051600430 | 0.5 | 50-160 | 21123A | 1,25 | 212 | 20 | 70 | 88 | 20 | 56 | 35 | 32 | 19 | 264 | 130 | 100 | 24 | 104 | 14.3 | 5 |
| 502300052800430 | 0.5 | 161-280 | 21124A | 1,25 | A+57 | 20 | 70 | 88 | 20 | 56 | 35 | 32 | 19 | 264 | 130 | 100 | 24 | 104 | 15.5 | 10 |
| 502300101600430 | 1 | 50-160 | 21143A | 1,25 | 212 | 20 | 70 | 88 | 20 | 51 | 40 | 32 | 24 | 264 | 130 | 100 | 24 | 104 | 14.3 | 10 |
| 502300102800430 | 1 | 161-280 | 22144A | 1,25 | A+57 | 20 | 70 | 88 | 20 | 51 | 40 | 32 | 24 | 264 | 130 | 100 | 24 | 104 | 15.5 | 10 |
| 502300201800430 | 2 | 64-180 | 21163A | 1,80 | 248 | 24 | 100 | 120 | 24 | 63 | 51 | 40 | 32 | 335 | 165 | 100 | 31 | 118 | 25.3 | 10 |
| 502300203000430 | 2 | 181-300 | 21164A | 1,80 | A+76 | 24 | 100 | 120 | 24 | 63 | 51 | 40 | 32 | 335 | 165 | 100 | 31 | 118 | 27.4 | 10 |
| 502300301800430 | 3 | 74-180 | 21173A | 2,20 | 262 | 28 | 114 | 137 | 30 | 78 | 57 | 46 | 35 | 380 | 180 | 165 | 37 | 130 | 38.2 | 10 |
| 502300303000430 | 3 | 181-300 | 21174A | 2,20 | A+89 | 28 | 114 | 137 | 30 | 78 | 57 | 46 | 35 | 380 | 180 | 165 | 37 | 130 | 41.2 | 10 |
| 502300501800430 | 5 | 82-180 | 21193A | 2,50 | 270 | 34 | 140 | 166 | 32 | 92 | 64 | 56 | 42 | 437 | 215 | 205 | 41 | 132 | 56.7 | 10 |
| 502300503000430 | 5 | 181-300 | 21194A | 2,50 | A+97 | 34 | 140 | 166 | 32 | 92 | 64 | 56 | 42 | 437 | 215 | 205 | 41 | 132 | 60.4 | 10 |

Blueprint

