

## Horizontal Lifting Clamp THSK

### Product information



Lifting clamp with adjustable extra large jaw opening for horizontal lifting, handling and transporting of stacks, packages and single steel plates. Terrier THSK lifting clamps must always be used in pairs (or multiple pairs).

The adjustable jaw offers wide variety of openings available from 3 to 420 mm.

#### Features:

- Easy adjustable jaw opening
- Quick and easy placing and removing of the clamp
- Lightweight design for easy handling
- Tough quality heavy duty welded body

... [Read more](#)

**Marking:** According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

**Temperature range:** - 40°C up to +100°C


**Standard:** EN 13155

**Note:** Must always be used in pairs (or multiple pairs)

**Warning:** Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm<sup>2</sup>)

## Horizontal Lifting Clamp THSK

### Blueprint



### Lifting table

| Part code       | Code         | WLL ton | Jaw width mm | V mm | S mm | W mm | T mm | H mm | U mm | X mm | Y mm | Z mm | Weight kg |
|-----------------|--------------|---------|--------------|------|------|------|------|------|------|------|------|------|-----------|
| 502100151800700 | 1.5 THSK/180 | 1.5     | 3-180        | 201  | 135  | 15   | 30,5 | 18   | 289  | 90   | 20   | 60   | 9.5       |
| 502100153000700 | 1.5 THSK/300 | 1.5     | 3-300        | 201  | 135  | 15   | 30,5 | 18   | 409  | 90   | 20   | 60   | 11        |
| 502100301800700 | 3 THSK/180   | 3       | 3-180        | 241  | 165  | 20   | 30,5 | 18   | 296  | 105  | 20   | 69   | 13        |
| 502100303000700 | 3 THSK/300   | 3       | 3-300        | 241  | 165  | 20   | 30,5 | 18   | 416  | 105  | 20   | 69   | 15        |
| 502100451800700 | 4.5 THSK/180 | 4.5     | 3-180        | 241  | 165  | 20   | 30,5 | 18   | 296  | 105  | 20   | 69   | 13        |
| 502100454200700 | 4.5 THSK/420 | 4.5     | 3-420        | 241  | 165  | 20   | 30,5 | 18   | 536  | 105  | 20   | 69   | 17        |
| 502100601800700 | 6 THSK/180   | 6       | 3-180        | 256  | 160  | 25   | 30,5 | 18   | 304  | 120  | 20   | 75   | 18        |
| 502100604200700 | 6 THSK/420   | 6       | 3-420        | 256  | 160  | 25   | 30,5 | 18   | 544  | 120  | 20   | 75   | 24        |
| 502100901800700 | 9 THSK/180   | 9       | 3-180        | 256  | 160  | 25   | 30,5 | 18   | 304  | 120  | 20   | 75   | 18        |
| 502100904200700 | 9 THSK/420   | 9       | 3-420        | 256  | 160  | 25   | 30,5 | 18   | 544  | 120  | 20   | 75   | 24        |