



Mobile crane



Piling crane



Steel Wire Rope verotop S

Product information

verope



Wire rope construction: verotop S is a very flexible rotation-resistant rope with compacted outer strands and very high breaking strength.

Features:

- Very strong compacted rotation-resistant rope.
- Achieves very good bending fatigue results.
- Offers excellent resistance to crushing and abrasion.
- Possesses perfect spooling behavior on multilayer drum.

ISO 4309 Rope Category No: All Diameters **RCN.23-2.**

Marking: According to standard

Standard: EN 12385-4

Note: verotop S can be used either with or without swivel.

Fill factor: 0.742

Tolerance Ø: +2% to +4%

Part Code	Rope diameter mm	Steel Area mm ²	Min. breaking force	Min. breaking force	Weight kg/100m	Total price
			kN 1960 N/mm ²	kN 2160 N/mm ²		
104101305070159	13	98	166	172.8	85	N/A
104101405070159	14	114	192.5	200.4	98	N/A
104101505070159	15	131	221	230.1	113	N/A

104101606270159	16	150	251.4	261.8	128	N/A
104101705270159	17	169	283.8	295.5	145	N/A
104101805070159	18	190	318.2	331.3	162	N/A
104101905070159	19	212	354.5	369.2	181	N/A
104102006070159	20	235	392.8	409	200	N/A
104102105270159	21	260	433.1	451	221	N/A
104102205070159	22	285	475.3	494.9	243	N/A
104102245070159	22.4	290	492.8	513.1	251	N/A
104102306270159	23	312	519.5	541	265	N/A
104102405270159	24	340	565.7	589	289	N/A
104102505070159	25	369	613.8	639.1	313	N/A
104102545070159	25.4	381	633.6	659.7	323	N/A
104102606270159	26	399	663.9	691.3	339	N/A
104102705070159	27	430	715.9	745.5	365	N/A
104102805070159	28	463	770	801.7	393	N/A
104102866070159	28.6	483	803.3	836.5	410	N/A
104102905270159	29	497	825.9	860	421	N/A
104103005070159	30	532	883.9	920.4	451	N/A
104103105070159	31	568	943.8	982.7	482	N/A