# Pipe and Test Sealing Bag

**Product information**




The sealing bags are suitable for all kind of pipe dimensions, models and materials. The operating preasure is between 0,5 til 6 bars depending on size and preasure in the pipe. Can be used to prevent or reroute sewagewater from reaching the groundwater or for bypass when reparing or preasure testing a pipe. Can also be used as a help when welding two pipes together by using the Vetter bag as a fix for the pipe ends.

All pipe sealing bags are available as test sealing bags with one or two bypasses. Need more information or help with choosing the correct model?  Please contact us.

... *Read more*

**Material:** Vulcanized reinforced rubber.
**Temperature range:** -20°C up to +90°C.
**Note:** For more information please contakt your CERTEX office.

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Pipe and Test Sealing Bag

## Lifting table

| Part code | Workingpressure bar | Pipe Ø mm | Cylinder Ø mm | Cylinderlength mm | Total length mm | Weight kg |
|---|---|---|---|---|---|---|
| 56111440000301 | 2,5 | 70-150 | 68 | 300 | 345 | 0.5 |
| 56111440011700 | 2,5 | 100-200 | 90 | 510 | 555 | 1.2 |
| 56111440016700 | 2,5 | 200-500 | 195 | 750 | 795 | 5 |
| 56111440000801 | 2,5 | 300-600 | 295 | 735 | 780 | 7 |
| 56111440028200 | 1,5 | 500-1000 | 450 | 1,110 | 1,155 | 17 |
| 56111480001901 | 1,5 | 600-1200 | 580 | 1,320 | 1,365 | 25 |
| 56111480006000 | 1,5 | 800-1400 | 785 | 1,810 | 1,855 | 41 |
| 56111400000300 | 0,5 | 1400-1700 | 1,350 | 1,900 | 2,150 | 55 |
| 56111400000100 | 0,5 | 1700-2000 | 1,620 | 1,900 | 2,300 | 59 |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved