

## Master Link Assembly X-006

### Product information



- Welded Master Link designed for 3-4 legs Chain, Wire Rope and Webbing Slings.
- The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.
- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Manufactured in accordance with EN 1677- 4 and ASME B30.26.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL  
... [Read more](#)

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.


**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

## Master Link Assembly X-006

### Blueprint



### Lifting table

Part code	Code	Chain diameter mm	WLL ton	EWL mm	Proof Load kN	Can be used up to single hook acc. to DIN 15401 no.	D mm	A mm	B mm	d mm	a mm	b mm	Weight kg
402100420410	BD-19 + 2 DD+13	6	4.2	189	103	5	19	135	75	13	54	25	1.3
402100820410	BD-22 + 2 DD+16	7-8	8.2	230	201	6	22	160	90	16	70	34	2.2
402101070410	BD-28 + 2 DD+19	10	10.7	265	262	8	28	180	100	19	85	40	3.9
402101570410	BD-32 + 2 DD+22	13	15.7	315	385	10	32	200	110	22	115	50	6.1
402102220410	BD-36 + 2 DD+28	16	22.2	325	544	16	36	260	140	28	140	65	10.6
402103410410	BD-50 + 2 DD+32	20	34.1	450	835	32	50	300	200	32	150	70	21.2
402104000410	BD-50 + 2 DD+36	22	40	470	980	32	50	300	200	36	170	75	23.8
402105600410	BD-60 + 2 DD+45	26	56	570	1,372	32	60	400	200	45	170	80	41.3