



## Welded Master Link Assembly X-0082

### Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.  
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.  
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	Chain diameter mm	WLL ton	EWL mm	Proof Load kN	For chain, 2-leg mm	Used to single hook acc. to DIN 15401 No.	D, A, B, d mm	a mm	b mm	Weight kg	Delivery time	
402100360440	ED-22	6	3.55	394	87	6,7,8	25	22 340 180	13	54	25	3.2	10
402100560440	ED-28	7-8	5.6	374	137	10	25	28 340 180	16	70	34	5.4	3
402100950440	ED-32	10	9.5	425	233	13	25	32 340 180	19	85	40	7.4	10
402101410440	ED-40	13	14.1	455	343	16	25	40 340 180	22	115	50	12.1	3
402102110440	ED-40	16	21.2	480	519	20	25	40 340 180	25	140	65	14.2	3

Blueprint

