



Master Link Grab 1 Assy X-A04, Yoke

Product information

Fully integrated shortening hook and master link.
At least 25% greater WLL than traditional Grade 8 products.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
No reduction in WLL when shortening chain.
Speedy assembly.
Light weight system.
Cost effective compared to slings which use multiple components.
Proof Load tested at 2.5 times the WLL with
certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL mm	DIN 15401 Hook No.	D mm	A mm	B mm	K mm	Weight kg	Delivery time
402100140460	6	1.4	120	4	13	120	70	196	0.7	5
402100250460	8	2.5	140	5	16	140	80	242	1.2	5
402100400460	10	4	160	6	19	160	95	285	2.1	5
402100670460	13	6.7	170	10	22	170	105	328	3.9	5
402101000460	16	10	190	10	28	190	110	392	7	10
402101600460	20	16	483	12	32	230	130	483	10	10
402101900460	22	19	591	20	38	275	150	591	14.4	10

Blueprint

