



Welded Master Link X-002W

Product information

- Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part code	Code	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	Din 15401.NO	A	B mm	D mm	Weight kg	Delivery time
402100280500	CD-13	2.8	120	7,8	6	4	120	70	13	0.4	10
402100400500	CD-16	4	140	10	7,8	5	140	80	16	0.7	10
402100670500	CD-19	6.7	160	13	10	6	160	95	19	1.1	5
402100850500	CD-22	8.5	170	13	10	10	170	105	22	1.6	10
402101150500	CD-28	11.5	190	16	13	10	190	110	28	2.9	10
402101700500	CD-32	17	230	20	16	12	230	130	32	4.5	10
402102510500	CD-36	25.1	275	22	20	20	275	150	36	6.7	5

Blueprint

