



## Welded Master Link X-002W

### Product information

- Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	Din 15401.NO	A mm	B mm	D, mm	Weight kg	Delivery time
402100280500	CD-13	2.8	120	7,8	6	4	120	70	13	0.4	10
402100400500	CD-16	4	140	10	7,8	5	140	80	16	0.7	10
402100670500	CD-19	6.7	160	13	10	6	160	95	19	1.1	3
402100850500	CD-22	8.5	170	13	10	10	170	105	22	1.6	10
402101150500	CD-28	11.5	190	16	13	10	190	110	28	2.9	10
402101700500	CD-32	17	230	20	16	12	230	130	32	4.5	10
402102510500	CD-36	25.1	275	22	20	20	275	150	36	6.7	3

## Blueprint

