Key Eye Point 8-291K

Product information

The lifting eye rotates through 360° adjustable in the direction of the load ... Read more




Features: Built-in RFID/NFC chip
Material: Alloy steel, quenched and tempered. Captive bolt with high WLL
Marking: According to standard, CE-marked
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Painted
Standard: EN 1677-1

Safety factor: 4:1
Grade: 10

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved

Key Eye Point 8-291K

Blueprint



Lifting table

Part code	WLL ton	Thread mm	Torque Nm	Pitch DIN 13	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	S mm	W mm	M mm	Weight kg
421100030620	0.3	M 8	10	1,25	38	25	9	9	12	25	24	6	41	6	44	M 8	0.1
421100040620	0.4	M 10	10	1,5	38	25	9	9	15	25	24	6	41	6	44	M 10	0.1
421100080620	0.75	M 12	10	1,75	45	30	10	11	18	33	30	9	47	8	52	M 12	0.2
421100150620	1.5	M 16	30	2	52	35	14	13	24	35	34	11	56	10	61	M 16	0.4
421100230620	2.3	M 20	70	2,5	60	40	16	15	30	44	37	15	65	12	70	M 20	0.6
421100320620	3.2	M 24	150	3	72	49	19	18	36	53	47	19	78	14	84	M 24	1.1
421100450620	4.5	M 30	350	3,5	91	61	24	22	45	62	59	23	95	17	105	M 30	2.1
421100700620	7	M 36	410	4	110	73	29	27	54	76	72	31	114	22	126	M 36	3.7
421100900620	9	M 42	550	4,5	128	83	34	32	63	89	81	38	132	24	147	M 42	5.8
421101200620	12	M 48	550	5	145	95	38	37	72	105	94	44	150	27	168	M 48	8.6
421101600620	16	M 56	800	5,5	148	102	40	43	84	124	92	49	166	27	178	M 56	11
421101800620	18	M 64	800	6	148	102	40	43	96	124	92	49	166	27	178	M 64	11.8

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved