

Eye Self Locking Hook X-025

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Eye Self Locking Hook X-025

Blueprint



Lifting table

| Part code | Chain diameter mm | WLL ton | EWL mm | A mm | D mm | H mm | K mm | P mm | T mm | Weight kg |
|--------------|-------------------|---------|--------|------|------|------|------|------|------|-----------|
| 402300140720 | 6 | 1.4 | 110 | 21 | 10 | 19 | 110 | 28 | 15 | 0.5 |
| 402300250720 | 7-8 | 2.5 | 136 | 25 | 11 | 24 | 136 | 34 | 20 | 0.8 |
| 402300400720 | 10 | 4 | 167 | 32 | 13 | 30 | 167 | 44 | 26 | 1.5 |
| 402300670720 | 13 | 6.7 | 207 | 40 | 16 | 39 | 207 | 51 | 30 | 3 |
| 402301000720 | 16 | 10 | 252 | 50 | 21 | 49 | 252 | 60 | 36 | 5.8 |
| 402301600720 | 20 | 16 | 290 | 60 | 23 | 65 | 290 | 70 | 53 | 10 |
| 402301900720 | 22 | 19 | 319 | 70 | 24 | 63 | 319 | 80 | 49 | 12.5 |
| 402302650720 | 26 | 26.5 | 343 | 80 | 25 | 69 | 343 | 99 | 56 | 15 |