



## Eye Sling Hook X-044/S

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2,5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-2

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	P1 mm	T mm	Weight kg	Delivery time
402300140010	6	1.4	20	10	19	80	23	17	0.3	5
402300250010	7-8	2.5	25	12	22	98	28	20	0.5	5
402300400010	10	4	33	15	30	122	36	23	1	5
402300670010	13	6.7	40	18	38	152	40	28	1.8	5
402301000010	16	10	51	22	44	185	44	36	3.4	5
402301600010	20	16	61	27	64	230	54	48	7.3	5
402301900010	22	19	51	31	61	245	76	52	9.3	10
402302650010	26	26.5	65	34	77	285	77	61	13.5	5
402304000010	32	40	91	41	79	358	114	65	22	10

## Blueprint

