



## Eye Grab Hook X-079

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- No reduction in WLL when shortening chain.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D mm	F mm	K mm	L mm	P mm	Weight kg	Delivery time
402300140760	5-6	1.4	76	8	18	9	24	76	99	12	0.24	5
402300250760	7-8	2.5	102	10	24	13	32	102	134	12	0.54	5
402300400760	10	4	125	12	31	14	40	125	163	15	1.03	5
402300670760	13	6.7	158	16	37	18	51	158	208	20	2.18	10
402301000760	16	10	202	19	48	24	64	202	264	21	4.39	5

**Blueprint**

