



## Eye Grab Hook X-041

### Product information

At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Painted.

**Standard:** EN 1677-1

**Note:** Not for use with Omega Link

**Safety factor:** 4:1

**Grade:** 10

| Part code    | Chain diameter mm | WLL ton | A mm | B mm | F mm | G mm | K mm | P mm | Weight kg | Delivery time |
|--------------|-------------------|---------|------|------|------|------|------|------|-----------|---------------|
| 402300140740 | 6                 | 1.4     | 13   | 7    | 26   | 8    | 50   | 8    | 0.2       | 5             |
| 402300250740 | 7-8               | 2.5     | 16   | 10   | 30   | 9    | 62   | 10   | 0.3       | 5             |
| 402300400740 | 10                | 4       | 20   | 13   | 40   | 13   | 82   | 13   | 0.6       | 5             |
| 402300670740 | 13                | 6.7     | 26   | 16   | 52   | 16   | 107  | 17   | 1.4       | 5             |
| 402301000740 | 16                | 10      | 30   | 18   | 70   | 20   | 132  | 21   | 2.4       | 5             |
| 402301600740 | 20                | 16      | 40   | 22   | 73   | 24   | 148  | 24   | 4         | 5             |
| 402301900740 | 22                | 19      | 42   | 24   | 86   | 26   | 166  | 26   | 5         | 5             |
| 402302650740 | 26                | 26.5    | 50   | 30   | 110  | 32   | 207  | 33   | 10.1      | 5             |

## Blueprint

