Eye Grab Hook with Pin X-0411

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof Load tested at 2.5 times the WLL with certification for each batch.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.
- Extra safe pin.

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-1
Note: Not for use with Omega Link.


Safety factor: 4:1
Grade: 10

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Eye Grab Hook with Pin X-0411

Blueprint



Lifting table

Part code	Chain diameter mm	WLL ton	Weight kg
402300250750	7-8	2.5	0.4
402300400750	10	4	0.7
402300670750	13	6.7	1.7

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved