



## Turnbuckle Jaw - Jaw Polar BN G-6333, Green Pin®

### Product information

Turnbuckle with jaw-jaw end-fitting and safety bolt for use under low temperatures, generally to ASTM F1145-92.

This turnbuckle can be used for rigging or tensioning wire, rope, rods etc. It is designed for in-line rigging, tensioning, or lashing and can be used in lifting applications.

**Standard:** Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

**Material:** Drop forged alloy steel, quenched and tempered

**Marking:** CE-marked

**Temperature range:** -40°C up to +200°C

**Finish:** Hot dipped galvanized

**Note:** Jaw ends up to and including 5/8" are fitted with bolts and nuts, sizes 3/4" and up are equipped with bolts, nuts and cotter pins

**Safety factor:** 5:1

**Grade:** 8

Part code	WLL ton	Take up inch	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg	Delivery time
422100100400	1	12	12	455	740	494	16	26	10	11	25	1.38	10
422100160400	1.59	12	16	498	774	557	18	32	13	14	33	2.32	10
422100240400	2.36	18	19	670	1,096	740	24	38	16	16	41	4.57	10
422100330400	3.27	18	22	713	1,132	790	27	42	19	19	48	6.5	10
422100450400	4.54	18	25	750	1,168	835	31	50	22	20	54	8.4	10
422100690400	6.9	18	32	805	1,230	910	44	71	28	26	68	13.6	10
422100970400	9.71	18	38	825	1,244	956	52	71	35	28	80	21.1	10
422101270400	12.7	18	45	938	1,316	1,092	60	86	41	33	90	30	10

Blueprint

