Solid Wire Rope Thimble Crosby S-412

Product information



Fits pin for open wire rope socket, boom pendant clevis and wedge socket ... *Read more*

Features: Greater protection against wear and deformation of the wire rope eye giving longer service life.
Material: Cast Ductile Iron.
Marking: Manufacturer's symbol.

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Solid Wire Rope Thimble Crosby S-412

Blueprint



Lifting table

Part code	Rope Ø range mm	A mm	B mm	C mm	D mm	D tolerance mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	Weight kg
123101300220	13	71.5	44.5	6.35	26.9	+-5%	19.1	14.2	7.1	22.4	54	41.4	39.6	0.28
123101600220	16	119	76	9.65	33.3	+-4%	26.9	20.6	10.4	28.7	86	57	65	1
123102000220	18-20	119	76	9.65	38.1	+-3%	26.9	20.6	10.4	35.1	86	57	65	1.05
123102200220	22	154	97	12.7	44.5	+-3%	35.1	26.9	13.5	41.4	114	82.5	87.5	2.47
123102600220	24-26	154	97	12.7	54	+-3%	35.1	26.9	13.5	46	114	82.5	87.5	2.38
123103000220	28-30	184	116	16	60.5	+-2%	44.5	33.3	16.8	52.5	137	98.5	103	4.21
123103500220	32-35	184	116	16	67	+-2%	49.3	38.9	19.8	58.5	137	98.5	105	4.45

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved