



## Solid Wire Rope Thimble Crosby S-412

### Product information

Fits pin for open wire rope socket, boom pendant clevis and wedge socket.

**Features:** Greater protection against wear and deformation of the wire rope eye giving longer service life.

**Material:** Cast Ductile Iron.

**Marking:** Manufacturer's symbol.

| Part code    | Rope Ø range mm | A,   | B,   | C,   | D,   | D tolerance | E,   | F,   | G,   | H,   | J,  | K,   | L    | Weight kg | Delivery time |
|--------------|-----------------|------|------|------|------|-------------|------|------|------|------|-----|------|------|-----------|---------------|
| 123101300220 | 13              | 71.5 | 44.5 | 6.35 | 26.9 | +5%         | 19.1 | 14.2 | 7.1  | 22.4 | 54  | 41.4 | 39.6 | 0.28      | 10            |
| 123101600220 | 16              | 119  | 76   | 9.65 | 33.3 | +4%         | 26.9 | 20.6 | 10.4 | 28.7 | 86  | 57   | 65   | 1         | 3             |
| 123102000220 | 18-20           | 119  | 76   | 9.65 | 38.1 | +3%         | 26.9 | 20.6 | 10.4 | 35.1 | 86  | 57   | 65   | 1.05      | 3             |
| 123102200220 | 22              | 154  | 97   | 12.7 | 44.5 | +3%         | 35.1 | 26.9 | 13.5 | 41.4 | 114 | 82.5 | 87.5 | 2.47      | 10            |
| 123102600220 | 24-26           | 154  | 97   | 12.7 | 54   | +3%         | 35.1 | 26.9 | 13.5 | 46   | 114 | 82.5 | 87.5 | 2.38      | 3             |
| 123103000220 | 28-30           | 184  | 116  | 16   | 60.5 | +2%         | 44.5 | 33.3 | 16.8 | 52.5 | 137 | 98.5 | 103  | 4.21      | 3             |
| 123103500220 | 32-35           | 184  | 116  | 16   | 67   | +2%         | 49.3 | 38.9 | 19.8 | 58.5 | 137 | 98.5 | 105  | 4.45      | 10            |

# Blueprint

