

Eye Grip Safe Locking Hook X-950

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Avoid finger injury by the grip design.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Eye Grip Safe Locking Hook X-950

Blueprint



Lifting table

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	D mm	H, mm	K mm	Omm mm	Pmm mm	T mm	Wmm mm	Weight kg
402300400850	10	4	175	33	13	31	176	49	71	27	137	1.9
402300670850	13	6.7	227	40	16	39	226	64	80	34	174	4
402301000850	16	10	277	50	21	47	277	78	114	39	212	6.3
402301600850	20	16	329	62	23	55	329	92	127	54	251	12.3
402302000850	22	19	350	70	24	59	350	98	151	56	258	14