

Swivel Grip Safe Locking Hook X-952N



Product information

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch. Built with ball bearing and enables full swivel feature under load.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Part Code	WLL ton	For chain Grade 10 Ø mm	A mm	B mm	D mm	H mm	K mm	O mm	P mm	T mm	W mm	Weight kg	Total price
11.16X-952N-10	4	10	41	34	16	31	225	49	71	27	139	2.4	N/A
11.16X-952N-13	6.7	13	46	44	21	39	285	57	80	34	174	5.2	N/A
11.16X-952N-16	10	16	61	50	23	47	345	78	114	39	212	8.4	N/A
11.16X-952N-20	16	20	74	82	25	56	433	91	127	54	250	14.5	N/A
11.16X-952N-22	19	22	97	95	33	59	475	105	151	56	260	19.9	N/A

Blueprint

