



## Swivel Self Locking Hook X-027N

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Rotate when loaded.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard

**Temperature range:** Tempering temperature minimum 400°C .

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | Chain diameter<br>mm | WLL<br>ton | A<br>mm | B<br>mm | D<br>mm | H<br>mm | K<br>mm | P<br>mm | T<br>mm | Weight<br>kg | Delivery time |
|--------------|----------------------|------------|---------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 420500140950 | 6                    | 1.4        | 32      | 23      | 12      | 19      | 149     | 28      | 15      | 0.7          | 5             |
| 420500250950 | 7-8                  | 2.5        | 36      | 29      | 13      | 24      | 186     | 34      | 20      | 1.2          | 5             |
| 420500400950 | 10                   | 4          | 41      | 35      | 16      | 30      | 218     | 44      | 26      | 2            | 5             |
| 420500670950 | 13                   | 6.7        | 46      | 44      | 21      | 39      | 276     | 51      | 30      | 4.1          | 10            |
| 420501000950 | 16                   | 10         | 61      | 50      | 23      | 49      | 329     | 60      | 36      | 7.2          | 10            |
| 420501600950 | 20                   | 16         | 74      | 82      | 25      | 65      | 403     | 70      | 53      | 13           | 5             |
| 420501900950 | 22                   | 19         | 97      | 96      | 33      | 63      | 454     | 80      | 49      | 20           | 10            |
| 420502650950 | 26                   | 26.5       | 123     | 116     | 51      | 69      | 535     | 99      | 56      | 33           | 10            |

## Blueprint

