



## Swivel Self Locking Hook X-027N

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Rotate when loaded.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard

**Temperature range:** Tempering temperature minimum 400°C .

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D, mm	H, mm	K mm	Pmm mm	T mm mm	Weight kg	Delivery time
420500140950	6	1.4	149	32	23	12	19	149	28	15	0.7	3
420500250950	7-8	2.5	186	36	29	13	24	186	34	20	1.2	3
420500400950	10	4	218	41	35	16	30	218	44	26	2	3
420500670950	13	6.7	276	46	44	21	39	276	51	30	4.1	10
420501000950	16	10	329	61	50	23	49	329	60	36	7.2	10
420501600950	20	16	387	74	82	25	65	403	70	53	13	10
420501900950	22	19	457	97	96	33	63	454	80	49	20	10
420502650950	26	26.5	535	123	116	51	69	535	99	56	33	10

## Blueprint

