


## Chain Sling CSX-176 Grade 10

---

### Product information



**Design:** Master link in one end and safety hook - clevis in the other end. Other combinations on demand.

**Dimension:** Ø 6–32 mm. (Other dimensions on demand).

... [Read more](#)

---

**Material:** Alloy steel grade 10.

**Marking:** According to standard, CE-marked

**Standard:** EN 818-4

**Note:** Hook with eye and link will be used for chain diameter 19-22 mm.

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

## Chain Sling CSX-176 Grade 10

### Lifting table

Part code	Code	Chain diameter mm	WLL ton
2406CSX1P06.10	CSX-176-06	6	1.4
2406CSX1P07.10	CSX-176-07	7	1.9
2406CSX1P08.10	CSX-176-08	8	2.5
2406CSX1P10.10	CSX-176-10	10	4
2406CSX1P13.10	CSX-176-13	13	6.7
2406CSX1P16.10	CSX-176-16	16	10
2406CSX1P19.10	CSX-176-19	19	14
2406CSX1P22.10	CSX-176-22	22	19
2406CSX1P26.10	CSX-176-26	26	26.5
2406CSX1P32.10	CSX-176-32	32	40