
Chain Sling CSX-176 Grade 10

Product information



Design: Master link in one end and safety hook - clevis in the other end. Other combinations on demand.
Dimension: Ø 6–32 mm. (Other dimensions on demand).

... *Read more*

Material: Alloy steel grade 10.
Marking: According to standard, CE-mark
Standard: EN 818-4
Note: Hook with eye and link will be used for chain diameter 19-22 mm.
Warning: Not to be heat-treated.

Safety factor: 4:1
Grade: 10

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Chain Sling CSX-176 Grade 10

Lifting table

Part code	Code	Chain diameter mm	WLL ton
2406CSX1P06.10	CSX-176-06	6	1.4
2406CSX1P07.10	CSX-176-07	7	1.9
2406CSX1P08.10	CSX-176-08	8	2.5
2406CSX1P10.10	CSX-176-10	10	4
2406CSX1P13.10	CSX-176-13	13	6.7
2406CSX1P16.10	CSX-176-16	16	10
2406CSX1P19.10	CSX-176-19	19	14
2406CSX1P22.10	CSX-176-22	22	19
2406CSX1P26.10	CSX-176-26	26	26.5
2406CSX1P32.10	CSX-176-32	32	40

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved