



## Material handling Hoist Red Rooster TCR

### Product information

Air chain hoist for material handling 250 kg.

These types Red Rooster Compact pneumatic driven Hoist are very suitable for "Material-Handling". The pendant control is direct on the lower hook so the operator can control and position the load easy and direct. The perfect solution for horizontal movements is the combination with a push trolley.

#### Standard features:

- Pendant control direct on the lower hook.
- Optimum load control, very precise positioning.
- One-hand control.
- Soft start and stop, no shock movements.
- Handle can be positioned for left-hand or righthand operation.
- Endstop system.

#### Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

**Marking:** CE-marked

Part code	WLL ton	Lifting height m	Type	Lowering speed with load m/min	Air consumption lowering (l/sec)	Lifting speed with max.load m/min	Weight at 3m HOL kg	Lifting speed without load m/min	Air consumption (l/sec)	Number of falls	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	Delivery time
5601TCR250ME	0.25	3	TCR-250ME	16	13	8	11	19	11.7	1	286	174	112	837	15	194	102	92	184	123	61	152	74	78	36	10

Lifting table

Blueprint

