



Master Link Assembly Pewag VWI Stainless

Product information

Stainless steel master link for 3- and 4-leg chainslings.

This stainless steel chain sling is electrically welded for a clean finish, stamped and ideally suited for assembling III- and IV-leg chain slings in welded or assembled systems. The dimensions are similar to DIN 5688-1.

The VWI Master link assembly is tested at 100 % of its load capacity. It is made from high-grade stainless steel with a higher resistance to acids and caustics than the standard four-leg chain slings G8, G10 and G12.

It is ideally suited for use in water and wastewater applications and can also be used in connection with chemicals and food products; however, restrictions will apply.

Material: 1.4404 (AISI 316L), 1.4462 (AISI 318LN).

Marking: CE-marked

Finish: Pickled and blasted.

Safety factor: 4:1

Grade: 6

Part code	Code	WLL ton	Consisting of	Usable up to sling hooks following DIN 15401 No.	d mm	mm	d1 mm	mm	e mm	mm	t mm	mm	t1 mm	mm	w mm	mm	w1 mm	mm	Weight kg	Delivery time
400100080070	VWI 4-6	0.84	AWI 10-6 + 2 BWI 9-6		10		9		124		80		44		50		20		0.28	10
400100130070	VWI 5-6	1.3	AWI 13-6 + 2 BWI 10-6		13		10		154		110		44		60		20		0.52	3
400100260070	VWI 6/7-6	2.6	AWI 16-6 + 2 BWI 13-6		16		13		164		110		54		60		25		0.91	10
400100340070	VWI 8-6	3.35	AWI 18-6 + 2 BWI 16-6		18		16		205		135		70		75		34		1.64	3
400100530070	VWI 10-6	5.25	AWI 22-6 + 2 BWI 20-6		23		20		245		160		85		90		40		3.02	10
400100890070	VWI 13-6	8.9	AWI 26-6 + 2 BWI 22-6		27		23		295		180		115		100		50		4.78	10
400101320070	VWI 16-6	13.2	AWI 32-6 + 2 BWI 26-6		32		27		340		200		140		110		65		7.98	10

Blueprint

