



## Connex Connecting Link Pewag CWI Stainless

### Product information

Stainless steel Connex connecting link, drop-forged and stamped.

This stainless steel connecting link is drop-forged and stamped and consists of two symmetrical halves made from high-grade stainless steel. The connecting link may be divided and used for the universal assembly of chain slings, master links, master link assemblies, shortenings, shackles and other accessories and is guaranteed to be compatible with all pewag winner inox components of the same nominal size. The suspension bolt is locked by a stainless steel coil spring (mat. 1.4462) with a synthetic leeve. The bolt and the shell are available as spare parts.

The product is suitable for straight pulling only; the simultaneous application of loads by two or more legs must be avoided. After the universally usable connecting link has been assembled and disassembled three times, it is recommended to use a new bolt and a new shell, to be mounted securely by a professional, to ensure that the quality of the product remains unimpaired. CBHWI spare part sets are available.

It is resistant to sea water and ideally suited for use in water and wastewater applications and can also be used in connection with chemicals and food products; however, restrictions will apply.

**Material:** 1.4462 (AISI 318LN).

**Marking:** CE-marked

**Finish:** Pickled and blasted.

**Safety factor:** 4:1

**Grade:** 6

Part code	Code	WLL ton	b mm	c mm	d mm	e mm	g mm	s mm	t mm	Weight kg	Delivery time
400200060040	CWI 5-6	0.63	34	7	7	36	13	10	11	0.06	3
400200090040	CWI 6-6	0.9	40	8	7	42	13	11	12	0.08	10
400200130040	CWI 7-6	1.25	51	9	9	54	17	13	14	0.14	3
400200160040	CWI 8-6	1.6	51	10	8,5	58	17	13	14	0.16	10
400200250040	CWI 10-6	2.5	70	13	13	73	25	18	18	0.37	3
400200430040	CWI 13-6	4.25	86	17	17	92	29	23	25	0.76	3
400200630040	CWI 16-6	6.3	105	21	20	104	37	32	28	1.41	3

## Blueprint

