



## Welded Master Link X-0080

### Product information

- Welded Master Link designed for 1 leg chain, wire rope and webbing slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL)

**Finish:** Blue Painted

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

| Part code    | Code  | Chain diameter | WLL<br>ton | EWL<br>mm | Proof Load<br>kN | Used to single hook acc. to DIN 15401 No. | D<br>mm | A mm | B mm | Weight<br>kg | Delivery time |
|--------------|-------|----------------|------------|-----------|------------------|---|---------|------|------|--------------|---------------|
| 402100670540 | ED-28 | 13             | 6.7        | 340       | 164              | 25  | 28      | 340  | 180  | 4.7          | 10            |
| 402101000540 | ED-32 | 16             | 10         | 340       | 245              | 25  | 32      | 340  | 180  | 6.2          | 5             |
| 402101900540 | ED-40 | 20-22          | 19         | 340       | 466              | 25  | 40      | 340  | 180  | 10           | 5             |

## Blueprint

