

## Swivel Hoist Ring 8-231 Long Bolt

---

### Product information



This swivel hoist ring rotates through 360° and pivots 180°, and simultaneously allows lifting from any direction.

- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolt are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.

[... Read more](#)

---

**Features:** Built-in RFID/NFC chip

**Material:** Forged alloy steel, quenched and tempered


**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Safety factor:** 4:1

## Swivel Hoist Ring 8-231 Long Bolt

### Blueprint



### Lifting table

Part code	WLL ton	Thread mm	Torque Nm	Pitch DIN13	A mm	B mm	C mm	D, mm	F mm	G, mm	Rmm mm	SWmm mm	E mm	Mmm mm	Weight kg
42158231007125L	0.7	M 10	60	1.5	33	41	29	11	80	58	17	17	103	M 10	0.4
42158231010150L	1	M 12	100	1.75	33	39	31	11	80	58	17	19	128	M 12	0.4
42158231020185L	2	M 16	150	2	50	54	46	17	116	90	27	24	149	M 16	1.1
42158231030230L	3	M 20	250	2.5	51	52	49	17	116	90	27	30	194	M 20	1.4
42158231050265L	5	M 24	400	3	72	81	59	25	163	126	37	36	221	M 24	3.2
42158231078340L	7.8	M 30	500	3.5	87	94	81	30	204	148	46	46	278	M 30	6.3
42158231125300L	12.5	M 36	1,000	4	110	112	98	36	248	188	57	55	225	M 36	10.9