# Swivel Hoist Ring 8-231 Long Bolt

## Product information



This swivel hoist ring rotates through 360° and pivots 180°, and simultaneously allows lifting  from any direction.

- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolt are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.

... *Read more*

**Features:** Built-in RFID/NFC chip
**Material:** Forged alloy steel, quenched and tempered
**Marking:** According to standard, CE-marked
**Standard:** EN 1677-1


**Safety factor:** 4:1

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

# Swivel Hoist Ring 8-231 Long Bolt

## Blueprint




## Lifting table

| Part code | WLL ton | Thread mm | Torque Nm | Pitch DIN13 | A mm | B mm | C mm | D mm | F mm | G mm | R mm | SW mm | E mm | M mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 42158231007125L | 0.7 | M 10 | 60 | 1.5 | 33 | 41 | 29 | 11 | 80 | 58 | 17 | 17 | 103 | M 10 | 0.4 |
| 42158231010150L | 1 | M 12 | 100 | 1.75 | 33 | 39 | 31 | 11 | 80 | 58 | 17 | 19 | 128 | M 12 | 0.4 |
| 42158231020185L | 2 | M 16 | 150 | 2 | 50 | 54 | 46 | 17 | 116 | 90 | 27 | 24 | 149 | M 16 | 1.1 |
| 42158231030230L | 3 | M 20 | 250 | 2.5 | 51 | 52 | 49 | 17 | 116 | 90 | 27 | 30 | 194 | M 20 | 1.4 |
| 42158231050265L | 5 | M 24 | 400 | 3 | 72 | 81 | 59 | 25 | 163 | 126 | 37 | 36 | 221 | M 24 | 3.2 |
| 42158231078340L | 7.8 | M 30 | 500 | 3.5 | 87 | 94 | 81 | 30 | 204 | 148 | 46 | 46 | 278 | M 30 | 6.3 |
| 42158231125300L | 12.5 | M 36 | 1,000 | 4 | 110 | 112 | 98 | 36 | 248 | 188 | 57 | 55 | 225 | M 36 | 10.9 |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved