



Swivel Hoist Ring 8-231 Long bolt

Product information



This swivel hoist ring rotates through 360° and pivot 180°, and simultaneously allows lifting from any direction.

- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolt are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.

Features: Built-in RFID/NFC chip

Material: Forged alloy steel, quenched and tempered

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Part Code	WLL ton	Torque Nm	Thread M mm	Thread length (E) mm	Pitch DIN13	A mm	B mm	C mm	D mm	F mm	G mm	H mm	R mm	S mm	SW mm	Weight kg	Total price
11.428-231-007/125L	0.7	60	M 10	103	1.5	33	41	29	11	80	58	23	17	6	17	0.4	N/A
11.428-231-010/150L	1	100	M 12	128	1.75	33	40	31	11	80	58	23	17	8	19	0.4	N/A
11.428-231-020/185L	2	150	M 16	149	2	50	54	46	17	117	90	36	27	10	24	1.1	N/A
11.428-231-030/230L	3	250	M 20	194	2.5	50	52	49	17	117	90	36	27	12	30	1.4	N/A
11.428-231-050/265L	5	400	M 24	221	3	72	81	59	25	163	125	44	37	14	36	3.2	N/A
11.428-231-078/340L	7.8	500	M 30	278	3.5	87	94	81	30	204	148	62	46	17	46	6.3	N/A
11.428-231-125/300L	12.5	1,000	M 36	225	4	110	112	98	36	247	188	75	57	22	55	10.9	N/A

Blueprint

