

Round Sling EXTREEMA® XS

Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- · Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m
- Standard with RFID

Material: HMPE -Dyneema®

Marking: According to standard, CE-marked Temperature range: -40 °C and +70 °C

Standard: EN 1492-2 except material

Safety factor: 7:1

| Part code | EWL m | WLL ton | Colour |
|-----------------|----------|------------|--------|
| 340500300050030 | 0.5 | 3 | Yellow |
| 340500300080030 | 0.75 | 3 | Yellow |
| 340500300100030 | 1 | 3 | Yellow |
| 340500300150030 | 1.5 | 3 | Yellow |
| 340500300200030 | 2 | 3 | Yellow |
| 340500300250030 | 2.5 | 3 | Yellow |
| 34050030030030 | 3 | 3 | Yellow |
| 340500300400030 | 4 | 3 | Yellow |
| 340500300500030 | 5 | 3 | Yellow |
| 340500500050030 | 0.5 | 5 | Red |
| 340500500100030 | 1 | 5 | Red |
| 340500500150030 | 1.5 | 5 | Red |
| 340500500200030 | 2 | 5 | Red |
| 340500500250030 | 2.5 | 5 | Red |
| 340500500300030 | 3 | 5 | Red |
| 340500500400030 | 4 | 5 | Red |
| 340500500500030 | 5 | 5 | Red |
| 340501000150030 | 1.5 | 10 | Orange |
| 340501000200030 | 2 | 10 | Orange |
| 340501000300030 | 3 | 10 | Orange |
| 340501000400030 | 4 | 10 | Orange |
| 340501000500030 | 5 | 10 | Orange |
| | | | |

Lifting table

| | V | | | | | |
|-----|----|-------------------------|------------------|--------------|--|--|
| | | Extreema® XS roundsling | | | | |
| | | HMPE EXS | | | | |
| WLL | SF | Core ø mm | Weight kg 3m EWL | p/m extra kg | | |
| 3t | 7 | 9 | 0,8 | 0,25 | | |
| 5t | 7 | 14 | 1,35 | 0,43 | | |
| 10t | 7 | 23 | 2 | 0,65 | | |
| 15t | 7 | 31 | 3,5 | 1,15 | | |
| 20t | 7 | 37 | 4,6 | 1,50 | | |