Round Sling Extreema® XS

Product information



The Extreema® XS sling is a compact high-strength round sling designed for lifting operations in confined or restricted spaces. It is used where traditional slings are too bulky or require larger hardware. Manufactured from HMPE, it combines high load capacity with a small diameter, enabling efficient and controlled lifting in tight environments.

WLL range: 3 – 20t
EWL range: 0,5m – 16m, (15t/20t can be made up to 65m)

When to choose this product

Best for:

- Lifting in confined spaces with limited clearance
- Applications requiring compatibility with standard shackles

Product benefits

- Compact diameter enables lifting in restricted or hard-to-reach areas
- D:d ratio 1:1 allows use with standard bow shackles
- HMPE construction provides high strength with low weight
- Lightweight design simplifies transport, handling, and storage
- Seamless sleeve supports durability and extended service life

... *Read more*

Material: HMPE
Marking: According to standard, CE-marked
Temperature range: -40°C up to +70°C
Standard: EN 1492-2
except material

Safety factor: 7:1

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Round Sling Extreema® XS

Lifting table

Part code	EWL m	WLL ton	Colour
340500300050030	0.5	3	Yellow
340500300080030	0.75	3	Yellow
340500300100030	1	3	Yellow
340500300150030	1.5	3	Yellow
340500300200030	2	3	Yellow
340500300250030	2.5	3	Yellow
340500300300030	3	3	Yellow
340500300400030	4	3	Yellow
340500300500030	5	3	Yellow
340500500050030	0.5	5	Red
340500500100030	1	5	Red
340500500150030	1.5	5	Red
340500500200030	2	5	Red
340500500250030	2.5	5	Red
340500500300030	3	5	Red
340500500400030	4	5	Red
340500500500030	5	5	Red
340501000150030	1.5	10	Orange
340501000200030	2	10	Orange
340501000300030	3	10	Orange
340501000400030	4	10	Orange
340501000500030	5	10	Orange

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved