

## Chain SMS - Half Long Link Grade 2

### Product information

Chain for different applications.

**Marking:** According to standard

**Finish:** 3 - 4.5 mm zink-plated, 5 mm hot-dip galvanized.

**Standard:** SMS 1503

**Warning:** Not for lifting.

**Grade:** 2



Part code	Chain diameter mm	Min. breaking force kN	Length m	Package	D, mm	E mm	Hmm mm	Weight kg/m	Delivery time
200100200250011	2	1.5	25	Bundle	2	15	3	0.07	10
200100250250011	2.5	2.3	25	Bundle	2.5	17	4	0.11	5
200100300250011	3	3.4	25	Bundle	3	19	5	0.16	10
200100350250011	3.5	4.6	25	Bundle	3.5	21	5.5	0.22	10
200100400250011	4	6	25	Bundle	4	23	6	0.28	10
200100450250011	4.5	7.5	25	Bundle	4.5	25	7	0.36	10
200100500250011	5	9.5	25	Bundle	5	28	8	0.45	5
200100550250011	5.5	11.5	25	Bundle	5.5	31	9	0.5	10
200100600250011	6	13.5	25	Bundle	6	35	10	0.6	10
200100700250011	7	18.5	25	Bundle	7	41	11	0.9	10
200100800250011	8	24	25	Bundle	8	47	13	1.1	10
200100900250011	9	32	25	Bundle	9	53	15	1.4	10
200101000250011	10	40	25	Bundle	10	59	16	1.7	10
200101100250011	11	46	25	Bundle	11	50	15	2.2	5
200101300250011	13	63	25	Bundle	13	55	20	3	10
200101600250011	16	96	25	Bundle	16	65	22	4.6	5

# Blueprint

