Chain DIN - Short Link Grade 3

Product information

Chain for different applications.

... *Read more*



Marking: According to standard
Finish: 3-4 mm zink-platined, 5- mm hot-dip galvanized.
Standard: DIN 766
Warning: Not for lifting.


Grade: 3

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Chain DIN - Short Link Grade 3

Blueprint



Lifting table

Part code	Chain diameter mm	Min. breaking force kN	Length m	Package	D mm	E mm	H mm	Weight kg/m
200500300500011	3	3.2	50	Bundle	3	16	5	0.16
200500400500011	4	8	50	Bundle	4	16	5,7	0.32
200500500300011	5	12.5	30	Bundle	5	18,5	7	0.5
200500600300011	6	16	30	Bundle	6	18,5	8,2	0.8
200500800150011	8	32	15	Bundle	8	24	11,2	1.4
200500900250011	9	40	25	Bundle	9	27	12,6	1.8
200501000150011	10	50	15	Bundle	10	28	14	2.2
200501100250011	11	63	25	Bundle	11	31	15,4	2.7
200501300250011	13	80	25	Bundle	13	36	18,2	3.8

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved