


## Steel Wire Rope PVC-coated 6x7-WSC Stainless

### Product information



General use



A stainless rope equipped with a Steel (WSC) and has a PVC-coating. It can be used for various applications such as locking rope, signaling devices, etc but not for lifting.

The PVC-coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

[... Read more](#)

**Rope construction:** 6x7-WSC

**Material:** AISI 316 / EN 1.4401

**Marking:** According to standard

**Temperature range:** -30°C up to +70°C

**Finish:** PVC-coated, see table for colour

**Standard:** EN 12385-4

*except material and coating*

**Note:** Peel off coating at end when making any end fittings such as clamping ferrules etc

**Fill factor:** 0,55

## Steel Wire Rope PVC-coated 6x7-WSC Stainless

### Lifting table

Part code	Rope diameter mm	Inner diameter mm	Colour	Tensile strength N/mm <sup>2</sup>	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
105120400300180	4	3	transparent	1,570	5.48	3.89	-	4.2
105120500400180	5	4	transparent	1,570	9.75	6.91	-	7.3
105120600400180	6	4	transparent	1,570	9.75	6.91	-	8.2
105120600400181	6	4	White	1,570	9.75	6.91	-	8.2
105120700500181	7	5	White	1,570	15.2	10.8	-	12.1
105120800400180	8	4	transparent	1,570	9.75	6.91	-	10.2
105120800500181	8	5	White	1,570	15.2	10.8	-	13.5
105120900600181	9	6	transparent	1,570	21.9	15.6	-	18.5