Chain - Short Link Grade 8

Product information

Chain for lifting and also allowed to use in lashing systems according to EN 12195-3.

... *Read more*



Material: Alloy steel.
Marking: According to standard
Finish: Painted.
Standard: EN 818-2
Warning: Not to be heat-treated.


Safety factor: 4:1
Grade: 8

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Chain - Short Link Grade 8

Blueprint



Lifting table

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	D mm	E mm	H mm	Weight kg/m
203100600000050	6	1.12	45.2	6	18	8.5	0.8
203100700000050	7	1.5	61.6	7	21	10.5	1.1
203100800000050	8	2	80.4	8	24	11.5	1.4
203101000000050	10	3.15	126	10	30	14	2.2
203101300000050	13	5.3	212	13	39	19	3.8
203101600000050	16	8	322	16	48	23	5.7
203102000000050	20	12.5	503	20	60	26	9
203102200000050	22	15	608	22	66	28,6	11
203102600000050	26	21.2	849	26	78	33,8	15
203103200000050	32	31.5	1,290	32	96	41,6	23

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved