

Weld-on Point 8-0573



Product information

Classic weld-on point without spring.












- Pivots through 180°.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts are traceable to Test Certification.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Lugs designed to assist the welding process.

Material: Forged alloy steel, quenched and tempered.
Marking: According to standard, CE-marked, WLL
Standard: EN 1677-1
Note: Never apply load except in the same direction with the pivot direction.

Safety factor: 5:1 (WLL 1-8 ton), 4:1 (WLL 10-30 ton)

Part code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L mm	W mm	HV mm	a mm	Weight kg	Delivery time
42158057320	20	186	93	100	25	37	175	70	105	234	91	20	4	6.5	10

Lifting table

	Kind of attachment									
	Number of legs	1	2	1	2	2	2	2	3-4	3-4
	Load direction	0°	0°	90°	90°	0-45°	45°- 60°	unsymm.	0 - 45°	45°- 60°
	Item No.	WLL(t)								
	8-0573-01	1.00	2.0	1.00	2.0	1.40	1.00	1.00	2.10	1.50
	8-0573-03	3.00	6.0	3.00	6.0	4.20	3.00	3.00	6.30	4.50
	8-0573-05	5.00	10.0	5.00	10.0	7.00	5.00	5.00	10.50	7.50
	8-0573-08	8.00	16.0	8.00	16.0	11.20	8.00	8.00	16.80	12.00
	8-0573-10	10.00	20.0	10.00	20.0	14.00	10.00	10.00	21.00	15.00
	8-0573-20	20.00	40.0	20.00	40.0	28.00	20.00	20.00	42.00	30.00
	8-0573-30	30.00	60.0	30.00	60.0	42.00	30.00	30.00	63.00	45.00
	8-057-1T	1.00	2.0	1.00	2.0	1.40	1.00	1.00	2.10	1.50
	8-057-3T	3.00	6.0	3.00	6.0	4.20	3.00	3.00	6.30	4.50
	8-057-5T	5.00	10.0	5.00	10.0	7.00	5.00	5.00	10.50	7.50
	8-057-8T	8.00	16.0	8.00	16.0	11.20	8.00	8.00	16.80	12.00
	8-057-10T	10.00	20.0	10.00	20.0	14.00	10.00	10.00	21.00	15.00
	8-082-04	4.00	8.0	4.00	8.0	5.60	4.00	4.00	8.40	6.00
	8-082-06	6.700	13.4	6.700	13.4	9.40	6.70	6.70	14.10	10.10
	8-082-10	10.00	20.0	10.00	20.0	14.00	10.00	10.00	21.00	15.00
	8-082-16	16.00	32.0	16.00	32.0	22.40	16.00	16.00	33.60	24.00
	8-082-30	31.50	63.0	31.50	63.0	44.10	31.50	31.50	66.20	47.30

Blueprint

