

## Regular Swivel EE Green Pin® G-7713, Eye-eye

### Product information



The Green Pin® EE Swivel is a swivel with eye-eye end-fittings. The swivel is made from high tensile steel and can be used under water. Galvanization of the Green Pin® EE Swivel ensures its long-term durability. The swivel is available in a range with a working load limit from 0.4 up to 20.5 ton.

Certification on request: 2.1, 2.2

**Standard:** Generally to US Federal Spec. RR-C-271, Type VII, Class 2 ... [Read more](#)


**Material:** High tensile steel, quenched and tempered

**Finish:** Hot dipped galvanised

**Safety factor:** 5:1

## Regular Swivel EE Green Pin® G-7713, Eye-eye

### Blueprint



### Lifting table

Part code	WLL ton	EWL mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg
422500040030	0.4	75	6	87	32	18	19	27	75	0.1
422500060030	0.6	90	8	107	41	21	25	32	91	0.18
422500100030	1.12	109	10	131	51	24	32	38	111	0.3
422500160030	1.63	138	13	164	64	33	38	51	138	0.6
422500240030	2.4	167	16	198	76	40	45	61	166	1.13
422500330030	3.3	183	19	221	89	45	51	67	183	1.79
422500450030	4.54	213	22	257	102	53	57	78	213	2.55
422500570030	5.7	245	25	298	114	59	64	86	248	4.06
422500820030	8.2	273	32	357	143	68	80	68	293	8.48
422502050030	20.5	425	38	541	198	110	122	110	465	25.7