

Load Lashing - Stainless

Product information

Certex offers a comprehensive range of stainless steel lashing, from 25 mm to 50 mm webbing in various lengths together with stainless steel ratchets and fittings. Stainless lashing is used in acid environment as well as where the risk of corrosion is high. Used in barns, silage pits and for marine use.

... [Read more](#)



Note: Standard is with double hook, but can also be supplied with other fittings. Can also be supplied with Dry-band which is water and dirt repellent for a longer life cycle. Contact Certex direc

Load Lashing - Stainless

Lifting table

| Part code | Code | LC kN | LC daN | MBL | Length | Band width mm | Design | STF daN |
|-----------|----------------------|----------|-----------|-----|--------|------------------|----------|------------|
| 7097 | Hobby 250 stainless | 2.5 | 250 | 0.5 | - | 25 | Two part | - |
| 7097 | Hobby 250 stainless | 5 | 500 | 1 | 5 | 25 | Loop | - |
| 7097 | Handy 1000 stainless | 10 | 1,000 | 1 | - | 25 | Two part | 200 |
| 7097 | Handy 1000 stainless | 20 | 2,000 | 2 | 5 | 25 | Loop | 200 |
| 7097 | Lorry 1500 stainless | 15 | 1,500 | 3 | - | 35 | Two part | 350 |
| 7097 | Lorry 1500 stainless | 30 | 3,000 | 6 | 10 | 35 | Loop | 350 |