Load Lashing - Stainless

Product information

Certex offers a comprehensive range of stainless steel lashing, from 25 mm to 50 mm webbing in various lengths together with stainless steel ratchets and fittings. Stainless lashing is used in acid environment as well as where the risk of corrosion is high. Used in barns, silage pits and for marine use.

... *Read more*



Note: Standard is with double hook, but can also be supplied with other fittings. Can also be supplied with Dry-band which is water and dirt repellent for a longer life cycle. Contact Certex direc

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Load Lashing - Stainless

Lifting table

Part code	Code	LC kN	LC daN	MBL ton	Length m	Band width mm	Design	STF daN
7097	Hobby 250 stainless	2.5	250	0.5	-	25	Two part	-
7097	Hobby 250 stainless	5	500	1	5	25	Loop	-
7097	Handy 1000 stainless	10	1,000	1	-	25	Two part	200
7097	Handy 1000 stainless	20	2,000	2	5	25	Loop	200
7097	Lorry 1500 stainless	15	1,500	3	-	35	Two part	350
7097	Lorry 1500 stainless	30	3,000	6	10	35	Loop	350

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved