Lifting Eye Nut DIN 582 Electro Galvanized

Product information




Material: Steel C15E
Marking: According to standard, WLL, manufacturer C15, thread & CE
Finish: Electro galvanized.
Standard: DIN 582
Warning: The lifting eyes shall be screwed tight against the surface. When two lifting eyes are used their mutual position shall result in the two eyes at the same level. Larger angle between the slings than 90° are not tolerated. Lifting eyes can not be assembled against a surface that differ essentially from a surface perpendicular to the direction of the lift.

Safety factor: 6:1

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved

Lifting Eye Nut DIN 582 Electro Galvanized

Blueprint



Lifting table

Part code	WLL ton	Thread	d1 mm	d2 mm	d3 mm	d4 mm	h mm	k mm	Weight kg/100pc
421100010070	0.14	M8	M8	20	36	20	36	8	5
421100020070	0.23	M10	M10	25	45	25	45	10	9
421100030070	0.34	M12	M12	30	54	30	53	12	16
421100120070	1.2	M20	M20	40	72	40	71	16	36
421100180070	1.8	M24	M24	50	90	50	90	20	72

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved