

Lifting Eye Bolt DIN 580

Product information



Material: Steel C15E.

Marking: According to standard, CE-marked, WLL, manufacturer C15, thread.

Finish: Electro galvanized.


Standard: DIN 580

Note: The lifting eyes shall be screwed tight against the surface. When two lifting eyes are used their mutual position shall result in the two eyes at the same level. Larger angle between the slings than 90° are not tolerated. Lifting eyes can not be assembled against a surface that differs essentially from a surface perpendicular to the direction of the lift.

Safety factor: 6:1

Lifting Eye Bolt DIN 580

Blueprint



Lifting table

Part code	WLL ton	Thread	d1 mm mm	d2 mm mm	d3 mm mm	d4 mm mm	h mm mm	k mm mm	l mm mm	Weight kg/100pc
421100010080	0.14	M8	M8	20	36	20	36	8	13	6
421100020080	0.23	M10	M10	25	45	25	45	10	17	11
421100070080	0.7	M16	M16	35	63	35	62	14	27	28
421100120080	1.2	M20	M20	40	72	40	71	16	30	44
421100460080	4.6	M36	M36	75	126	70	128	28	54	265
421100630080	6.3	M42	M42	85	144	80	147	32	63	403
421100860080	8.6	M48	M48	100	166	90	168	38	68	638

Lifting Eye Bolt DIN 580

Thread	<input type="text"/>	<input type="text"/>
	WLL (ton)	
M8	0.14	0.095
M10	0.23	0.17
M12	0.34	0.24
M16	0.7	0.5
M20	1.2	0.83
M24	1.8	1.27
M30	3.2	2.6
M36	4.6	3.7
M42	6.3	5
M48	8.6	6.1