

TEC12

Product information



Typical application: Mooring, towing and anchor

Specific Gravity: 0.94 (Float)

Melting Point: 165°C

Water Absorption: None

Ultra-violet Light Resistance: Good

Abrasion Resistance: Good

[... Read more](#)


Rope construction: 12-strand (12x1)

Material: High tenacity polyolefin fiber

Finish: Blue/White

TEC12

Blueprint



Lifting table

Part code	Diameter mm	MBL ton	Length m	Rope ends	Weight kg/220m
301203602200071	36	29.6	220	Eye in both ends	141.02
301204002200071	40	36.3	220	Eye in both ends	174.02
301204402200071	44	43.5	220	Eye in both ends	214.94
301204802200071	48	50.9	220	Eye in both ends	251.9
301205202200071	52	58.8	220	Eye in both ends	294.8
301205602200071	56	67.3	220	Eye in both ends	343.2
301206002200071	60	77	220	Eye in both ends	393.8
301206402200071	64	86.6	220	Eye in both ends	448.8
301206802200071	68	98.4	220	Eye in both ends	506
301207202200071	72	109.4	220	Eye in both ends	567.6
301208002200071	80	134.1	220	Eye in both ends	701.8
301208802200071	88	161.3	220	Eye in both ends	849.2
301209602200071	96	190.3	220	Eye in both ends	569.8