

## Roundsling - Side Stitch

### Product information



**Design:** Load carrying yarn covered with color coded double protection sleeve.

**Stretch with working load:** 2-3%.

**Length tolerance:** Nominal length (EWL)  $\pm 2\%$ .

**Material:** Polyester. Resistant to most acids but not to strong alkalizes.

**Marking:** According to standard, The slings are provided with a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instruction.

**Temperature range:** app.  $-40^{\circ}$  -  $+100^{\circ}\text{C}$ .

**Standard:** EN 1492-2

**Safety factor:** 7:1.

<b>Part code</b>	<b>WLL ton</b>	<b>Colour</b>
34010010XXX0020	1	Violet
34010020XXX0020	2	Green
34010030XXX0020	3	Yellow
34010040XXX0020	4	Grey
34010050XXX0020	5	Red
34010060XXX0020	6	Brown
34010080XXX0020	8	Blue
34010100XXX0020	10	Orange
34010120XXX0020	12	Orange
34010150XXX0020	15	Orange
34010200XXX0020	20	Orange
34010250XXX0020	25	Orange
34010300XXX0020	30	Orange
34010340XXX0020	34	Orange
34010400XXX0020	40	Orange
34010500XXX0020	50	Orange
34010600XXX0020	60	Orange
34010800XXX0020	80	Orange
34011000XXX0020	100	Orange

**Blueprint**

