# Roundsling Assembly RR-176

## Product information



**Design:** Roundsling covered with extra protection sleeve and provided with strengthen eye in each end, assembled as tool in combination with lifting details in grade 8. Max manufacturing length 20 m.

**Stretch with working load:** 2-3%.

**Length tolerance:** Nominal length ±2%.

**Safety factor:** Forge 4:1 and round sling 7:1.

... *Read more*

**Material:** Polyester. Resistant to most acids but not strong alkalizes.
**Marking:** According to standard, The slings are provided with a label with manufacturer's symbol, working load limit (WLL) and CE marking.
**Temperature range:** app. -40° - +100°C.
**Standard:** EN 1492-2

**Grade:** 10

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

# Roundsling Assembly RR-176

## Lifting table

| Part code | WLL ton | Colour |
|---|---|---|
| 3403 | 1 | Violet |
| 3403 | 2 | Green |
| 3403 | 3 | Yellow |
| 3403 | 4 | Grey |
| 3403 | 5 | Red |
| 3403 | 6 | Brown |
| 3403 | 8 | Blue |
| 3403 | 10 | Orange |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved