

D Shackle 316 Stainless



Product information



Design: Stainless steel D shackle, with pin. Good for lifting applications where a high level of corrosion resistance is required. Typical applications: Water utility installations & other corrosive facilities, Pump chains and pump lifting, Chemical installations - Chlorine plants etc, General lifting in off-shore applications, General lifting and tethering in leisure marine applications, General lifting purposes.

Proof load: 2x WLL

Material: Stainless Steel EN10088 1.4404 (Marine Grade 316L)

Marking: WLL, CE, Supplier,

Finish: Polished

Safety factor: : 6:1

Part Code	WLL ton	P mm	B mm	J mm	L mm	Weight kg	Delivery time
420100010120	0.13	4	4	8	16	0.01	5
420100020120	0.2	5	5	10	20	0.01	10
420100030120	0.33	6	6	13	25	0.02	10
420100050120	0.5	8	8	16	32	0.05	10
420100080120	0.8	9,5	9,5	19	38	0.1	10
420100100120	1	11	11	22	44	0.15	10
420100130120	1.25	12,7	12,7	26	52	0.24	10
420100170120	1.66	16	14,3	29	58	0.45	5
420100230120	2.33	19	16	32	64	0.59	5
420100350120	3.5	22,2	19	38	76	1	5
420100450120	4.5	25,4	22,2	44	88	1.9	10
420100550120	5.5	28,6	25,4	51	102	2.9	10
420100650120	6.5	31,8	28,6	57	114	3.1	10
420100750120	7.5	34,9	31,8	64	128	4.35	10
420100900120	9	38	34,9	70	140	5.3	10

Blueprint

