

## Bow Shackle 316 Stainless



### Product information



**Design:** Stainless steel bow shackle, with pin. Good for lifting applications where a high level of corrosion resistance is required. Typical applications: Water utility installations & other corrosive facilities, Pump chains and pump lifting, Chemical installations - Chlorine plants etc, General lifting in off-shore applications, General lifting and tethering in leisure marine applications, General lifting purposes.

**Proof load:** 2x WLL

**Material:** Stainless Steel EN10088 1.4404 (Marine Grade 316L)

**Marking:** CE-marked, WLL, Supplier,

**Finish:** Polished

**Safety factor:** 6:1

<b>Part Code</b>	<b>WLL ton</b>	<b>B mm</b>	<b>J mm</b>	<b>L mm</b>	<b>P mm</b>	<b>W mm</b>	<b>Weight kg</b>	<b>Delivery time</b>
420100010130	0.13	4	8	16	4	12	0.009	10
420100020130	0.2	5	10	22	5	16	0.014	10
420100030130	0.26	6	13	28	6	19	0.028	5
420100040130	0.4	8	16	35	8	25	0.059	5
420100060130	0.63	9.5	19	38	9.5	28	0.06	5
420100080130	0.8	11	22	46	11	33	0.161	10
420100100130	1	12.7	26	52	12.7	38	0.27	5
420100130130	1.33	14.3	29	60	16	43	0.5	10
420100200130	2	16	32	68	19	50	0.63	10
420100280130	2.75	19	38	76	22.2	57	1.05	10
420100380130	3.75	22.2	44	88	25.4	66	1.995	10
420100450130	4.5	25.4	51	102	28.6	76	3.045	10
420100550130	5.5	28.6	57	114	31.8	86	3.255	10
420100650130	6.5	31.8	64	128	34.9	95	4.568	10
420100750130	7.5	34.9	70	140	38	105	5.565	10

# Blueprint

